

DECLARATION OF CONFORMITY

No. 005-06-2025 EN

FALIDA2® Facade screw



1. Unique identification code of the product type	FALIDA2® Facade screw
2. Mark for identification of the construction product in accordance with Article 11(4)	type description: see product packaging
3. Intended use of the construction product in accordance with the applicable harmonised technical specification	Screws for wood fastening
4. Manufacturer	FIXINGGROUP GmbH Austria
5. System of assessment and verification for constancy of performance	SYSTEM 3
6. Harmonised standard and notified body	EN 14592:2008+A1:2012 HFB Engineering NB1034
7. Declared performance	according to the table below

Declared performance				Ø 4,0 mm
Testing	Formula symbols	Unit	Specification	Results
Pull-out parameters	$f_{ax,k}$	N/mm ²	charact. Value	12,90
Density	ρ	kg/m ³	Mean value	422,0
head pull-through parameter	$f_{head,k}$	N/mm ²	charact. Value	16,90
Density	ρ	kg/m ³	Mean value	371,0
Tensile strength	$f_{tens,k}$	N	charact. Value	4.574
Torsional strength	$f_{tor,k} / R_{tor,k} \geq 1,5$	Nm	charact. Value	achieved
Yield moment	$M_{ly,k}$	Nm	charact. Value	2,25
Material	A2	-	-	1.4567

Dimensions				
Outer thread diameter	d mm	4,0 +0,2/-0,1	lb	
Head diameter	dk mm	5,7 +0,2/-0,2	2,7 +0,2/-0,2	
Total and thread length	L L1 mm +/- 0,5 mm	30 18	50 28	
		35 21	55 31	
		40 24	60 34	
		45 26	70 40	

The stated performance of the specified products is in accordance with the declaration of conformity according to Section 7 and the manufacturer is solely responsible for compiling this declaration of conformity according to Section 4.

Signed on behalf of the manufacturer, 16.06.2025

Günther Gaisbauer

Günther Gaisbauer