



PRODUCT DATASHEET

FALIDA® facade screw

16.06.2025 This copy is not subject to the print or paper form



FIXINGGROUP GmbH

www.fixinggroup.com

office@fixinggroup.com

1. Unique identification code of the product type	FALIDA2 facade screw
2. Label for identification of the product	Type description: See product packaging
3. Intended purpose of use	Screws for wood fastening
4. Manufacturer	FIXINGGROUP GmbH
5. Test method for evaluating and monitoring performance	System 3
6. Harmonized standard - CE declaration	EN 14592:2008 + A1:2012
7. Declared performance	CE declaration of conformity Nr. 005-06-2025

General information	
1.1. Fastening type	Direct fastening
1.2 Material	Stainless steel A2 - 1.4567 Stainless steel A2 - 1.4567 with black coating Mechanical and chemical wear of the black surface coating cannot be excluded

Dimensions				
Outer thread diameter	d mm	4,0 +0,2/-0,1	lb	
Head diameter Drive TX15	dk mm	5,7 +0,2/-0,2	2,7 +0,2/-0,2	
Total and thread length	L L1 mm +/- 0,5 mm	30 18	50 28	
		35 21	55 31	
		40 24	60 34	
		45 26	70 40	

FOR INTERNAL USE ONLY

All statements are based on our current knowledge and experience - no guarantee can be derived from our statements.

The suitability of the product for a specific application can only be guaranteed by our own tests and trials. Installation is in accordance with the manufacturer's specifications, Tips and tricks, installation instructions, technical rules, guidelines and country-specific regulations. The correct processing and installation of our products is beyond our control and therefore not our responsibility. Errors, modifications of the product range and technical changes are reserved.