



PRODUCT DATASHEET

TERA® fence and privacy screen hardware and fittings

25.03.2024 This copy is not subject to the print or paper form



FIXINGGROUP GmbH

www.fixinggroup.com

office@fixinggroup.com

1. Unique identification code of the product type	TERA PA 19-23 Post Connection Profile TERA PA 24-27 Post Connection Profile TERA SP Stability Profile TERA AP Finishing Trim TERA ASP 19-23 Top Cap Profile TERA ASP 24-27 Top Cap Profile
2. Label for identification of the product	Type description: See product packaging
3. Intended purpose of use	fence and privacy screen hardware and fittings
4. Manufacturer	FIXINGGROUP GmbH
5. Harmonized standard - CE declaration of conformity mark	Not subject to declaration of conformity

General information	
1.1. Material	Extruded aluminium profile EN AW-6060 T66 [EN755]
1.2 Surface finish	- Silver anodized E6/EV1 - Powder coated RAL 7016
1.3 Dimensions	Profile length 1.800 mm Tolerance -0/+10 mm The technical drawings show the following dimensions: TERA ASP 19-23: Top flange width 25 mm, top flange thickness 1.5 mm, vertical height 33 mm. TERA ASP 24-27: Vertical height 37.5 mm. TERA PA 19-23: Top flange width 25 mm, top flange thickness 1.5 mm, vertical height 32.5 mm, bottom flange width 50 mm, bottom flange thickness 8 mm, bottom flange width 18 mm, bottom flange thickness 1.5 mm, bottom flange width 16 mm, bottom flange thickness 2.0 mm, bottom flange width 23 mm. TERA PA 24-27: Vertical height 37 mm, bottom flange width 15 mm, bottom flange thickness 27.5 mm. TERA SP: Bottom flange width 18 mm, bottom flange thickness 1.5 mm, bottom flange thickness 8 mm. TERA AP: Bottom flange width 15 mm.

FOR INTERNAL USE ONLY

All statements are based on our current knowledge and experience - no guarantee can be derived from our statements.

The suitability of the product for a specific application can only be guaranteed by our own tests and trials. Installation is in accordance with the manufacturer's specifications, Tips and tricks, installation instructions, technical rules, guidelines and country-specific regulations. The correct processing and installation of our products is beyond our control and therefore not our responsibility. Errors, modifications of the product range and technical changes are reserved.